

## 5800 Transmitters

### Door/Window Transmitters



The 5800 Series of door and window transmitters provide the most reliable, convenient and cost effective solutions for security protection. These devices are powerful and versatile enough to help solve even the toughest, most labor intensive installations.

With a demonstrated outdoor range of over a mile, the 5800 Series has the best performance of any transmitters available today.

## FEATURES

### **5814 Ultra Small Door/Window Transmitter**

The 5814 provides the perfect solution for difficult to reach places and applications where aesthetics and small size are important.

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Features a built-in reed switch and tamper
- Includes replaceable lithium coin cell battery
- Dimensions:  
1-1/2" H x 1-3/16" W x 5/8" D

### **5815 Door/Window Transmitter**

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient, and cost-effective solution for door and window protection.

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Battery: 3V Lithium
- Dimensions:  
3" H x 1-1/2" W x 7/8" D

### **5816 Door/Window Transmitter**

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR)
- Dimensions:  
3-1/16" H x 1-9/16" W x 1-3/16" D

### **5816MN Door/Window Transmitter**

Two zone transmitter with both built-in magnetic reed switches [90° apart] and wired closed circuit contact loop.

- Features a small design for a hidden professional look
- Dimensions:  
3-1/16" H x 1-1/2" W x 15/16" D

# 5800 Transmitters

## Door/Window Transmitters



## FEATURES

### 5817 Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports normally open and normally closed applications and fast loop response time. The two auxiliary loops support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5msec
- Dimensions:  
3-1/2" H x 1-9/16" W x 1-3/16" D

### 5817CB Universal Contact-Monitoring Transmitter

The 5817CB is a universal contact-monitoring transmitter that can be used with household and commercial fire and burglary-initiating devices.

- The 5817CB has three unique input loops (zones)
- The first loop (primary loop) is supervised and typically used for high-priority alarm reporting such as commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with magnet
- The third loop is another normally closed household burglary loop. All three loops may be used
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CB
- Dimensions:  
3-1/2" H x 1-9/16" W x 1-3/16" D

### 5818 Recessed Transmitter

Contact sensor that provides concealed protection for a door or window.

- Features a tapered cylinder for easy and flush fit
- Includes self-contained transmitter, reed sensor, battery & recessed magnet
- Features a standard white plastic case; brown cases available (5818BR); plastic cover-up plug included
- Use 7/8" drill bit for transmitter
- Use 1/2" drill bit for magnet
- Dimensions:  
13/16" diameter, 4-7/8" long  
(Magnet) 1/2" diameter, 1-3/4" long

## ORDERING

<b>5814</b>	Ultra Small Door/Window Transmitter
<b>5815</b>	Door/Window Transmitter
<b>5816MN</b>	Door/Window Transmitter
<b>5816</b>	Door/Window Transmitter
<b>5817</b>	Three Zone Universal Transmitter
<b>5817CB</b>	Three Zone Universal Transmitter
<b>5818</b>	Recessed Transmitter

## Honeywell Security & Custom Electronics

PO Box 9035,  
Syosset, NY 11791

[www.security.honeywell.com/sce](http://www.security.honeywell.com/sce)

# Honeywell

L/5820trans/D  
October 2004  
©2004 Honeywell International Inc.