



An ADEMCO Group Company

# 748 SERIES

Dual Tone Sirens and  
Speaker Version

sounders

## ADEMCO introduces 3 new sounders.

- ◆ 748LC – 112db Output Siren @ 550 mA
- ◆ 748 – 119db High Output Siren
- ◆ 749 – Speaker Version/8 ohms/20 watts



*Now you can find the perfect choice for small to large jobs. The 748LC is loud, yet offers low power consumption. Where maximum power output is required, try the 748. It often eliminates the need for installing multiple sounders.*

*These fully tampered and weather-resistant sounders mount directly to a 4" electrical box or wall – eliminating the need for a cabinet. Priced below other sounders, the compact design of these attractive units make installation easier than ever before – indoors or out.*





An ADEMCO Group Company

# 748 SERIES

## Specifications

### The **ASC** Edge:

- ◆ Significantly louder 119db (748) output, 112db (748LC) output
- ◆ Smaller...mounts directly to wall or standard 4" electrical box
- ◆ Dual tone output...steady and warble
- ◆ Ready to mount...no disassembly required
- ◆ Tamper proof and weather resistant
- ◆ Attractive, can be used indoors or outdoors



### 748/748 LC Specifications:

<b>Housing:</b>	Durable weather resistant ABS plastic with UV protection
<b>Dimensions:</b>	105mmW x 116mmH x 92mmD
<b>Operating Temperature:</b>	-20°F to 175°F
<b>Operating Voltage:</b>	6-14 VDC
<b>Current Draw:</b>	748 – 1200mA @ 12 VDC 748LC – 550mA @ 12 VDC
<b>Speaker:</b>	8 ohms, 25W peak
<b>Sound Pressure:</b>	748 – Warble/steady 119dB min. @ 12 VDC (at 1 meter) 748LC – Warble/steady 112dB min. @ 12 VDC (at 1 meter)
<b>Tamper Switch:</b>	Normally closed when mounted (opens on alarm)
<b>Weight:</b>	1.5 lbs. max

### 749 Speaker/Horn Specifications:

8 ohms/20 watts, 25W peak

Housing, dimensions and other specifications are identical to the 748/748LC Dual Tone Sirens

**Easy Mounting**

Mounts directly to wall or standard 4" electrical box as shown. Mounting hardware included.